

??????? 2

Поменять <SERVER>, <USER> и <PASSWORD> на свои значения FTP сервера

```
/system scheduler
add disabled=no interval=5d name=backup on-event=backup policy=\
  ftp,reboot,read,write,policy,test,password,sniff,sensitive,romon \
  start-date=jan/10/2020 start-time=00:00:01
/system script
add dont-require-permissions=no name=backup owner=su policy=\
  ftp,reboot,read,write,policy,test,password,sniff,sensitive,romon source="/\
  log info "\"backup starting\"";\r\
  \n:local CurrentTime [/system clock get time];\r\
  \n:local CurrentDate [/system clock get date];\r\
  \n:local Hour [:tostr [:pick \"$CurrentTime 0 2]]; \r\
  \n:local Min [:tostr [:pick \"$CurrentTime 3 5]]; \r\
  \n:local Day [:tostr [:pick \"$CurrentDate 4 6]]; \r\
  \n:local Month [:tostr [:pick \"$CurrentDate 0 3]]; \r\
  \n:local Year [:tostr [:pick \"$CurrentDate 7 [:len \"$CurrentDate]]]; \r\
  \n:global name=backupfile value=([/system identity get name] .\"__\$Day_\$\\
  Month_\$Year__\$Hour_\$Min.backup\")\r\
  \n:global name=scriptfile value=([/system identity get name] .\"__\$Day_\$\\
  Month_\$Year__\$Hour_\$Min.rsc\")\r\
  \n/system backup save name=\$backupfile;\r\
  \n/export verbose file=\$scriptfile;\r\
  \n:delay 10s\r\
  \n/tool fetch address=<SERVER> src-path=\$backupfile user=<USER>\
  r mode=ftp password=<PASSWORD> dst-path=\"backup/\$backupfil\
  e\" upload=yes;\r\
  \n/tool fetch address=<SERVER> src-path=\$scriptfile user=<USER>\
  r mode=ftp password=<PASSWORD> dst-path=\"backup/\$scriptfil\
  e\" upload=yes;\r\
  \n:delay 20s\r\
  \n/file remove \$backupfile;\r\
  \n/file remove \$scriptfile;\r\
  \n/log info "\"backup finished\"";\r\
  \n"
```

Версия #3

Ivan Tiukov создал 2 декабря 2021 14:51:46

Ivan Tiukov обновил 2 декабря 2021 18:33:38