

Вариант 2

Поменять <SERVER>, <USER> и <PASSWORD> на свои значения FTP сервера

```
/system scheduler
add disabled=no interval=5d name=backup on-event=backup policy=\
  ftp,reboot,read,write,policy,test,password,sniff,sensitive,romon \
  start-date=jan/10/2020 start-time=00:00:01
/system script
add dont-require-permissions=no name=backup owner=su policy=\
  ftp,reboot,read,write,policy,test,password,sniff,sensitive,romon source="/\
  log info "backup starting";\r\
  \n:local CurrentTime [/system clock get time];\r\
  \n:local CurrentDate [/system clock get date];\r\
  \n:local Hour [:tostr [:pick \${CurrentTime} 0 2]];\r\
  \n:local Min [:tostr [:pick \${CurrentTime} 3 5]];\r\
  \n:local Day [:tostr [:pick \${CurrentDate} 4 6]];\r\
  \n:local Month [:tostr [:pick \${CurrentDate} 0 3]];\r\
  \n:local Year [:tostr [:pick \${CurrentDate} 7 [:len \${CurrentDate}]]];\r\
  \n:global name=backupfile value=([/system identity get name] .\"__\${Day}_\${
  Month}_\${Year}__\${Hour}_\${Min}.backup\")\r\
  \n:global name=scriptfile value=([/system identity get name] .\"__\${Day}_\${
  Month}_\${Year}__\${Hour}_\${Min}.rsc\")\r\
  \n/system backup save name=\${backupfile};\r\
  \n/export verbose file=\${scriptfile};\r\
  \n:delay 10s\r\
  \n/tool fetch address=<SERVER> src-path=\${backupfile} user=<USER>\
  r mode=ftp password=<PASSWORD> dst-path=\"backup/\${backupfil\
  e\" upload=yes;\r\
  \n/tool fetch address=<SERVER> src-path=\${scriptfile} user=<USER>\
  r mode=ftp password=<PASSWORD> dst-path=\"backup/\${scriptfil\
  e\" upload=yes;\r\
  \n:delay 20s\r\
  \n/file remove \${backupfile};\r\
  \n/file remove \${scriptfile};\r\
  \n/log info "backup finished";\r\
  \n"
```

Revision #3

Created 2021-12-02 14:51:46 UTC by Ivan Tiukov

Updated 2021-12-02 18:33:38 UTC by Ivan Tiukov